

CLEANING HD WALLS VINYL BASED DIGITAL MURALS



1.0 GENERAL CONDITIONS, REMOVING DAY-TO-DAY SOIL

Ordinary dirt and smudges can be removed with a mild soap and warm water. Clean from bottom of wall upward. Rinse thoroughly with clean water from the top down using a sponge. Deeply embossed wallcoverings need extra attention to remove suds or loosened dirt that may lodge in the embossing. Dry wallcovering with a soft lint free cloth or towel.

For more difficult stains that are only surface deep, the use of a stronger detergent is recommended. Always test an inconspicuous area with the stronger detergent to be sure that the surface and ink are not damaged.

DO NOT USE steel wool or powdered abrasives because they can damage the image and textured surface.

DO NOT USE solvents, alcohol, pine oil, or cleaners that contain these kinds of products as they can remove the image and damage the textured surface.

When cleaning, always take measures to prevent water from dripping behind molding.

NEVER MIX CLEANING AGENTS TOGETHER, VIOLENT REACTIONS MAY OCCUR.

2.0 SURFACE PROTECTION

HD walls prints using durable UV inks that are easily cleaned and highly resistant to abrasion from surface contact.

We recommend DreamGuard Protex 3 for an extra measure of protection where surfaces are exposed to frequent collisions, scuffing, food stains, etc. DreamGuard Protex 3 is a water-based, non-hazardous topcoat that can be applied with commercial liquid laminating equipment as well as with a paint roller. Surfaces treated with DreamGuard Protex3 are significantly more durable in heavy wear areas.